



Products in comparison	Analog	testo Smart Probes AC & refrigeration test kit	testo 549	testo 550	testo 557	testo 570
Identical pressure measuring range HP/LP	–	Up to 60 bar	Up to 60 bar	Up to 60 bar	Up to 60 bar	Up to 50 bar
Pressure measurement accuracy	> 1 % of f.v.	> 0.5 % of f.v.	> 0.5 % of f.v.	> 0.5 % of f.v.	> 0.5 % of f.v.	> 0.5 % of f.v.
Integrated temperature measurement	–	✓	✓ (Up to 2 temperature probes)	✓ (Up to 2 temperature probes)	✓ (Up to 2 temperature probes)	✓ (Up to 3 temperature probes)
Four-way valve manifold	Product-dependent	–	–	–	✓	✓
Internal memory, documentation	–	With the App	–	With the App	With the App	✓
Refrigerants stored	max. 4	> 80	60	60	60	40
Refrigerant update by customer	–	Possible on site via App	–	Possible on site via App	Possible on site via App	Via testo EasyKool software
Automatic ambient pressure measurement	–	–	–	–	✓	✓
Heat pump mode	–	–	✓	✓	✓	✓
Temperature-compensated leakage testing	–	–	✓	✓	✓	✓
Vacuum measurement	–	–	Indication	Indication	Highly precise, with external probe	Accurate and robust
Via testo EasyKool software	–	–	–	–	–	✓
App and Bluetooth	–	✓	–	✓	✓	–