

We measure it.



## rpm measuring instrument

**testo 465 – Non-contact rpm measurement**

---

Easy one-hand operation

---

Storage of mean/min./max. values as well as last measurement value

---

Measurement distance up to 600 mm

---

Robust design thanks to SoftCase (protective cover)

---



With the testo 465, you can measure rpm easily without contact using only one hand. The measuring instrument is thus suitable for measurements on rotating parts such as ventilators and shafts. Simply attach a reflective marker (optional) to the measurement object, point the visible red beam of light at the reflective marker, and measure. The

distance to the measurement object is up to 600 mm. The measuring instrument stores mean, min. and max. values as well as the last measurement value. The SoftCase included in delivery protects the instrument from impact, ensuring an especially long working life.

## Technical data / Accessories

### testo 465

testo 465 RPM measuring instrument with transport case incl. reflectors and batteries

Part no. 0563 0465



#### Sensor type

#### Optically with mod. light beam

|                      |                                                                   |                                |
|----------------------|-------------------------------------------------------------------|--------------------------------|
| Meas. range          | +1 to +99999 rpm                                                  |                                |
| Accuracy<br>±1 digit | ±0.02% of mv                                                      |                                |
| Resolution           | 0.01 rpm<br>(+1 to +99.99 rpm)<br>0.1 rpm<br>(+100 to +999.9 rpm) | 1 rpm<br>(+1000 to +99999 rpm) |

#### General technical data

|               |                                 |
|---------------|---------------------------------|
| Oper. temp.   | 0 to +50 °C                     |
| Storage temp. | -20 to +70 °C                   |
| Battery type  | 2 AA batteries or rech. battery |
| Display       | 5-figure LCD display, 1-line    |
| Weight        | 145 g                           |
| Warranty      | 2 years                         |
| Dimensions    | 144 x 58 x 20 mm                |
| Battery life  | 40 h                            |

### Accessories

### Part no.

#### Accessories for measuring instrument

|                                                                                                                          |           |  |
|--------------------------------------------------------------------------------------------------------------------------|-----------|--|
| Reflectors, self-adhesive (1 pack = 5 off, each 150 mm long)                                                             | 0554 0493 |  |
| ISO calibration certificate/rpm<br>optical and mechanical rpm measuring instruments; cal. points 500; 1000; 3000 rpm     | 0520 0012 |  |
| ISO calibration certificate/rpm<br>optical rpm measuring instruments; calibration points 10; 100; 1000; 10000; 99500 rpm | 0520 0022 |  |
| ISO calibration certificate/rpm<br>Calibration points freely selectable from 10 to 99500 rpm                             | 0520 0114 |  |
| DAkkS calibration certificate/rpm<br>Optical rpm probes, 3 points in instrument measurement range (1 to 99,999 rpm)      | 0520 0422 |  |

We measure it.



Testo NV  
Industrielaan 19  
1740 Ternat  
Tel. 02/582 03 61  
Fax 02/582 62 13  
Email: [info@testo.be](mailto:info@testo.be)

[www.testo.be](http://www.testo.be)

Al onze prijzen zijn nettoprijzen, excl. BTW (21%) en verzendingskosten, geldig van 01.01.2015 tot 31.12.2015. Wijzigingen, ook van technische aard, voorbehouden.